


|              |                                                            |
|--------------|------------------------------------------------------------|
| Product name | Patch SPX 1xSC/UPC-LC/UPC 2m SM G657A2 White 4mm LSZH FTTx |
| Product code | 5072413                                                    |
| GTIN         | 7332811143151                                              |
| ETIM-Class   | EC001263                                                   |



PRODUCT SPECIFICATIONS

Fiberoptic patch cord singlemode G657A2 with white 4mm simplex cable and SC/UPC-LC/UPC connectors.

Halogen-free according to EN 60754-1/2 and flame-retardant according to IEC 60332-2-2. Meets the requirements of IEC 61300, EN186000-1, EIA/TIA-455 and TELCORDIA GR-326-CORE/GR-63.

ID marked with a unique number for full traceability and delivered with individual measurement protocols.

Measurements

|        |        |
|--------|--------|
| Length | 210 mm |
| Height | 15 mm  |
| Width  | 180 mm |
| Weight | 33 g   |

Technical Specifications - Connectors

|                                           |        |
|-------------------------------------------|--------|
| Max insertion loss per connector (UPC)    | 0.2 dB |
| Max Optical Return Loss for UPC connector | -55 dB |
| Radius of Curvature UPC                   | 7-12   |

Technical Specifications - Patch Cords

|                                              |                               |
|----------------------------------------------|-------------------------------|
| Length                                       | 2                             |
| Fibre Type                                   | ITU-T G.657 A2                |
| Outer Sheath Material                        | LSZH (Low Smoke Zero Halogen) |
| Colour of Cable Sheath                       | White                         |
| Cable Diameter                               | 4 mm                          |
| Temperature ranges for Operation             | -40°C to +85°C                |
| Temperature ranges for transport and storage | -40°C to +85°C                |
| Halogen Free                                 | Yes                           |