

Product name	Microduct ID 7x12/10mm WHITE HFFR with HFFR jacket D500m
Product code	85700407
GTIN	7332811116032
ETIM-Class	EC001474



PRODUCT SPECIFICATIONS

HFFR microducts are designed for long term protection of fiber optical cables and are especially suitable for installation of micro cables. Indoor microducts are used for indoor installation applications with a sheath and primary ducts made of halogen-free, flame retardant material. Parameters such as flexibility and higher safety levels for fire and dangerous substances makes it optimized for safe and effective indoor installations. Every microduct has a permanent, co-extruded silicone compound inner liner giving a coefficient of friction of less than 0,1.

Measurements

Length	1,000 mm
Height	35 mm
Width	38 mm
Weight	505 g

Technical Specifications - Single Ducts

Duct Type	12/10
Duct Colour	White
Outer Diameter	12 mm
Outer Diameter Tolerance	+/- 0.1 mm
Inner Diameter	10 mm
Inner Diameter Tolerance	+/- 0.1 mm
Min Bending Radius	120 mm

Max Install Tensile Force	340 N
Inner clearance test (of ID)	85 %
Weight	59 kg/km
Outer/inner surface quality (PN 64-004-99)	Without Deformation
Longitudinal reversion (EN ISO 2505)	max 3%
Density (EN ISO 1183)	1.55 +/- 0.1
Blowing pressure	16 Bar

Technical Specifications - Bundle

Bundle Type	7-way
Tube Colour Sequence	Number Sequenced
Sheath Colour (Bundle)	White
Sheath Thickness	0.8 mm
Bundle Dimensions	37.6 x 34.4 mm
Min Bending Radius (Bundle)	376 mm
Max Install Tensile Force (Bundle)	2,380 N

Mechanical Characteristics

Temperature ranges for installation	+5°C - +45°C
Temperature ranges for Operation	-40°C - +70°C
Temperature ranges for transport and storage	-20°C - +45°C
Pressure Withstand (EN 1167-1,2)	Resistance to internal pressure (23°C, 16 bar, 2 h)
Tensile performance (IEC 60794-1-21, Method E1)	Compliant
Kinking (IEC 60794-1-21, Method E10)	Compliant
Crush (IEC 60794-1-21, Method E3A)	Compliant
Impact (IEC 60794-1-21, Method E4)	Compliant
Bending (IEC 60794-1-21, Method E11B)	Compliant
Coefficient of Friction (IEC 62470)	ˆ 0,1
Torsion IEC-60794-1-21-E7	Tension around a curve of 1040mm with cof <0.1
ESCR Test (ASTM D1693)	Condition b>500h with min 5 ok out of 10

Flame Retardant Test Compliance

Flammability Compliance	EN 60332-3-23 category B, EN 60332-3-10
Smoke Density	IEC 61034-2
Halogen Content	IEC 60754-1, 0%
UL 94 (EN 60695-11-10)	V-0
Limiting oxygen index (ISO 4589-2)	Min. 32%

Droplets

No material dripping at burning